


WARNING!



Be sure electrical power is OFF before and during installation or maintenance.
The luminaire must be installed by a qualified electrician, in accordance with all applicable local codes.

Ensure that the rated luminaire voltage requirements are compatible with the available mains supply in which it will be installed.
All LEDs are included in your lamp. Never touch the LED surface with your bare hands as this may reduce the life of your LED.
Do not alter, relocate or remove any electrical component.



Line: ORBIT
Family: PENDANT LAMP
Description: ORBIT ACCORD PENDANT LAMP 1426

Material: Natural Wood Veneer, MDF and Frosted glass Globe
Weight:

ASSEMBLING THE FIXTURE

Read carefully all the Assembly Instructions below, before starting the installation process.

Turn OFF the power before start the installation.

- ① Remove the protecting package from the pieces taking care to not harm any parts with cutting surfaces or objects. Lay the parts of the fixture on some horizontal surface in order to connect them, if needed use the protecting package to soften the surface and protect the parts from getting scratched or harmed.
- ② Install a mini-LED bulb (A15) on the E-26 socket and then make the assembling of the glass globe on the aluminum base, holding carefully the two metallic tabs and inserting the globe one side at a time below the tabs. Release carefully the tabs, one at a time, so that they keep the globe fixed in place.

INSTALLING THE FIXTURE ON CEILING

- ③ Insert the electrical cable through the disk (c), conical cable gland, nipple, canopy and crossbar.
- ④ Adjust the length of the electrical cable by attaching a knot to keep the luminaire at the desired height.
- ⑤ Connect the power supply wires to the junction, in accordance with applicable local standards, as shown in the diagram opposite.
- ⑥ Screw the junction box cover (A) and crossbar (B) into the junction box using the screws provided.

ADJUSTING THE FIXTURE HEIGHT

- ⑦ After making the electrical connection, insert the excess wire into the junction box.
- ⑧ Bring the canopy to the ceiling and secure it by screwing the conical thread pass with the nipple to the crossbar, until everything is safe on the ceiling.

Turn ON electrical power.

Your luminaire is now ready for use.

ATTENTION!



FAILURE TO COMPLY WITH THESE INSTRUCTIONS MAY CAUSE ACCIDENTS AND LOSS OF PRODUCT WARRANTY.
It's recommended to read these instructions completely and carefully before proceeding.

SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE.

ACCORD Lighting guarantees coverage against manufacturing defects including electrical components and finishes, for a period of three years, under normal use, from the date of purchase. For warranty service, please contact your local dealer for further instructions. Proof of date of purchase will be required for validation of warranty service.

The responsibility of the manufacturer regarding the product warranty is related to the correct observation of the instructions contained in this manual. The manufacturer is not responsible for any damage to the product caused by accidents, alterations of any kind, improper usage or improper installation. See the website for additional warranty details.

ACCORD Lighting reserves the right to change the dimensions and specifications contained in this manual without prior notice, in accordance with its policy of continuous product improvement. Please, contact the manufacturer if additional information is necessary. The illustrations in this manual are for guidance only and may vary in scale, dimensions and model details.